


SERIES BS1776

SUB-MINIATURE SILICON HIGH VOLTAGE RECTIFIER





PART NUMBER	PIV VOLTS	I_O AMPS 50° C	V_f @ I_O @ 25° C	I_r @ PIV @ 25° C	MAX SINGLE CYCLE SURGE CURRENT	T_{rr}
BS1776-20	2000	1.5	4.5	10 μ A	250 AMPS	150 nSec
BS1776-25	2500	1.5	6.0	10 μ A	250 AMPS	150 nSec
BS1776-30	3000	1.5	6.0	10 μ A	250 AMPS	150 nSec
BS1776-40	4000	1.25	7.5	10 μ A	250 AMPS	150 nSec
BS1776-50	5000	1.0	10.5	10 μ A	250 AMPS	150 nSec
BS1776-60	6000	.75	12.0	10 μ A	250 AMPS	150 nSec

Maximum Ambient Operating Temperature -55° C to $+125^{\circ}$ C

Recovery Time: .5 Amp Forward to 1 Amp Reverse Recover to .25 Amp

OUTPUT CURRENT vs AMBIENT TEMPERATURE



(203) 467-2591 TEL
 (203) 469-5928 FAX
 Email: Info@edal.com
 Internet: <http://www.edal.com>

EDAL[®] INDUSTRIES
INC. SINCE 1958
 51 Commerce St. East Haven, CT 06512